



Product Service

# CERTIFICATE

No. Z1 12 10 78929 003

**Holder of Certificate:** Rail Safety Systems BVWethouder Hillenstraat 4  
5913 RT Venlo  
THE NETHERLANDS**Certification Mark:****Product:****Safety divider  
Rail Safety Systems Spoormagnet**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

**Test report no.:**

RV84496T, RV83106T

**Date,** 2012-10-11

( Alfred Beer )

Page 1 of 2



Product Service

**CERTIFICATE****No. Z1 12 10 78929 003****Model(s):****S207 TUV  
S205 Tube ALU  
S212 Tube GRP****Parameters:**

a. Rail fastening S207 TUV:  
 M440 TUV Basic holder:  
 40x40x2 = 1300 profile for mounting  
 Material Steel (S235JRG2)  
 Magnet: M448 210x80x70mm, plastic carrier,  
 material POM Zwart (black) UV prot.  
 396: 200x41x25mm, Magnet

LS003: Angle holder (diagonal/vertical):  
 - M400 TUV 40x40x2H = 1160mm,  
 material steel (S235JRG2)  
 - M447 45x45x1,5 l = 260  
 (Slider) material steel (S235JRG2)  
 - M445 Plate with thread material steel  
 (S235JRG2)  
 - M446 Clamp 110x70x20mm,  
 material POM Zwart (black) UV Prot

b1. Tube S206 4 meter or S205 3 meter  
 M433 Tube Lock Buis (tubing) dia. 48.3x3 l=2000 or  
 M432 Tube Lock Buis (tubing) dia. 48.3x3 l=1500  
 M436 One end with coupling P1502 Tube Lock Koppeling  
 man(coupling male) 3,2  
 M435 Second end with coupling P1501 Tube Lock Koppeling  
 Vrouw (coupling female) 3,2  
 Tube lock, general wallthickness: 5mm

b2. Tube S212 4 meter of 3 meter,  
 M435 P-1501 rev.C (3.2) Tube-lock vrouw,  
 M436 P-1502 rev.C (3.2) Tube-lock man 2000,  
 M476 Ring Press

**Tested  
according to:**

PPP 65001:2011

**Production  
Facility(ies):**

78887

Page 2 of 2